

EAGLE GREEN PE SINGLE/DUAL WALL

Eco-Friendly/Non-Pressure Rated
Recycled HDPE Corrugated Pipe



DELIVERING GOOD WATER TO YOU

MARKETS



Drainage



Irrigation

PRODUCT INFO



SINGLE WALL

Shall be joined together using snap and/or split couplers. Full line of soil tight fittings available upon requests.


Nominal Laying Length:
10 feet

(Laying length tolerances are in accordance with ASTM standards)
(Coil Option: Available upon request)

PIPE COLOR ● Black

PIPE SIZES

4" • 6"



ADDITIONAL OPTIONS

Perforated*
Coil*

PRODUCT INFO



DUAL WALL

Features an integral bell and dual spigot for superior water-tight (10.8 psi) connection. Full line of water-tight fabricated fittings are available upon request.


Nominal Laying Length:
20 feet

(Laying length tolerances are in accordance with ASTM standards)

PIPE COLOR ● Black

PIPE SIZES

4" • 6" • 8" • 10" • 12" • 15" • 18"
24" • 30" • 36" • 42" • 48" • 60"



ADDITIONAL OPTIONS

Perforated*

CERTIFICATIONS

ASTM F2648/F667
ASTM D3350 Cell Class 424420C/E
435400C/E

GASKETS

ASTM F477

INTEGRAL BELL JOINT

ASTM D3212

BENEFITS

MADE IN AMERICA

INSTALLATION

SINGLE WALL / DUAL WALL

- Lightweight, long laying length, easy transportation and installation.
- Feature dual crown corrugation for greater pipe stiffness.
- Extremely durable. Corrosive, gouging, abrasive resistant.

FEATURES

DUAL WALL

- Superior strength-to-weight ratio.
- 100 years design life per Florida DOT.
- Flexible design supports H-25 live loads with a minimum cover of 1 foot, (except 60-inch: 2-foot cover).



* Please call prior to order regarding availability.

EAGLE GREEN PE SINGLE/DUAL WALL


Eco-Friendly/Non-Pressure Rated
Recycled HDPE Corrugated Pipe



SUBMITTAL AND DATA SHEET

SINGLE WALL PIPE FOR USE IN GRAVITY FLOW DRAINAGE

NOM I.D. IN (MM)	APPROX. O.D. (IN)	PIPE STIFFNESS (PSI)	APPROX. WGT (LBS/FT)
4 (100)	4.732	36	0.35
6 (150)	6.870	36	0.90



PRODUCT STANDARD

ASTM F667

PIPE COMPOUND

ASTM D3350 Cells Class 424420C/E

ADDITIONAL OPTIONS

Perforated*, Coil*

NOMINAL LAYING LTN.

10 FEET

(Laying length tolerances are in accordance with ASTM standards)


INSTALLATION

ASTM D2321

JM Eagle™ Eagle Corr PE Installation Guide

DUAL WALL PIPE FOR USE IN GRAVITY FLOW DRAINAGE

NOM I.D. IN (MM)	APPROX. O.D. (IN)	PIPE STIFFNESS (PSI)	APPROX. WGT (LBS/FT)
4 (100)	4.732	50	0.4
6 (150)	6.870	50	1.1
8 (200)	9.110	50	1.7
10 (250)	11.420	50	2.5
12 (300)	14.280	50	3.2
15 (375)	17.490	42	4.8
18 (450)	20.830	40	6.3
24 (600)	27.530	34	11.2
30 (750)	34.630	28	15.8
36 (900)	41.530	22	20.9
42 (1050)	47.425	20	26.9
48 (1200)	53.835	18	34.0
60 (1500)	66.660	14	56.0



PRODUCT STANDARD

ASTM F2648

PIPE COMPOUND

ASTM D3350 Cell Class 424420C/E

ASTM D3350 Cell Class 435400C/E

GASKET

ASTM F477

INTEGRAL BELL JOINT

ASTM D3212

ADDITIONAL OPTIONS

Perforated*

NOMINAL LAYING LTN.

20 FEET

(Laying length tolerances are in accordance with ASTM standards)

INSTALLATION

ASTM D2321

JM Eagle™ Eagle Corr PE Installation Guide

Manning Coefficient (n) = 0.012



*Please call prior to order regarding availability.

This information may have been updated. Please visit www.jmeagle.com for all updated information and warranty details.

CUSTOMER SERVICE - 1.800.621.4404

THIS PRODUCT IS MADE IN AMERICA

UPDATED JULY 2022