



MODERN
INFRASTRUCTURE
MADE IN AMERICA

THREADED DROP PIPE/WELL CASING LOADING CHART

LOADING CHART

PRODUCT TYPE	SIZE	LENGTH	PCS/LIFT	FT/LIFT	LIFTS/LOAD	% LOAD	FT/LOAD
DROP PIPE SCH80 PHA* 20' LENGTH	1	20	250	5,000	36	2.78%	180,000
	1 1/4	20	200	4,000	28	3.57%	112,000
	1 1/2	20	150	3,000	28	3.57%	84,000
	2	20	100	2,000	28	3.57%	56,000
DROP PIPE SCH80 PSU* 20' LENGTH	1	20	120	2,400	40	2.50%	96,000
	1 1/4	20	100	2,000	40	2.50%	80,000
	1 1/2	20	90	1,800	40	2.50%	72,000
	2	20	53	1,060	40	2.50%	42,400
DEEP DROP PIPE SCH120 SCH120 20' LENGTH	1	20	120	2,400	40	2.50%	96,000
	1 1/4	20	100	2,000	40	2.50%	80,000
	1 1/2	20	90	1,800	40	2.50%	72,000
	2	20	53	1,060	40	2.50%	42,400
PVC WELL CASING (INCLUDES EAGLE LOC) 20' LENGTH	2	20	105	2,100	28	3.6%	58,800
	4	20	57	1,140	12	8.3%	13,680
	4 (West)*	20	29	580	28	3.6%	16,240
	4 1/2	20	26	520	24	4.2%	12,480
	5	20	23	460	20	5.0%	9,200
	5 (West)*	20	23	460	24	4.2%	11,040
	6	20	20	400	16	6.3%	6,400
	6 (West)*	20	20	400	20	5.0%	8,000
	8	20	15	300	12	8.3%	3,600
	8 (West)*	20	20	400	12	8.3%	4,800
	10	20	12	240	12	8.3%	2,880
	12 (West)*	20	6 / 8	120 / 160	8 / 8	5.4 / 7.1 %	2,240

Lifts/Load based on unit size—Do not Exceed Maximum Weight per Truckload: 45,000 lbs.

* Threaded drop pipe made only in PHA (Hastings, NE) and PSU (Sunnyside, WA) facilities.

Each facility has different unit quantities for SCH80 due to regional market demand.

No stock transfers performed on this product.